



NOTE.

- 1. + CONDUCTORS ARE TO BE SOLID, 600 VOLT 250°C, 12 GAUGE MIN. WIRES DIRECTLY CONNECTED TO THE ELEMENT TERMINALS. NO TERMINAL LEGS, OR 250°C 600V, 12 GA. STRANDED WIRE USING NICKEL PLATED STEEL TERMINALS.

BUS BAR
PIN 1319800

THIS APPLIANCE MUST BE CONNECTED TO 220V. OR 240V. AS SPECIFIED.

TOTAL KW LOAD	THREE PHASE KW PER PHASE			SINGLE PHASE			NOMINAL AMPERES PER LINE		
	L1	L2	L3	L1	L2	L3	L1	L2	L3
22.24	11	5.5	5.5	12	6	6	100	50	25
22.24	11	5.5	5.5	12	6	6	100	50	25
22.24	11	5.5	5.5	12	6	6	100	50	25
22.24	11	5.5	5.5	12	6	6	100	50	25

ITEM	PART NUMBER	PART NAME	MATERIAL	BLANK SIZE	FINISH
	1032300	BROILER ELEMENT	1375 WATT	220V.	
	1032301	BROILER ELEMENT	1500 WATT	240V.	
	1010701	SWITCH			
	1160797	LAMP ASS'Y	RED		
	1026202	CIRCUIT BREAKER	40 AMP.	240V.	
	1671491	WIRING DIAGRAM			

REV	SYM	DESCRIPTION	DATE	APP
02		RELEASED ITEM #1	11/10/79	
TOLERANCES (EXCEPT AS NOTED)		SCALE		
FRACTIONAL ± 1/64 DECIMAL ± .005		SCALE		
GILBERT COMMERCIAL INDUSTRIES, INC.		DWG SIZE	B	
PRELOND, PENNSYLVANIA 18824		DO NOT SCALE		
TITLE:		DATE	DRWN	APP
36 ES 30 BB		1/10/89	GU	
36 ET 30 BB		DRAWING NO.	REV	
220/380 VOLT, 50 HZ		16714	0	
240/415 VOLT, 50 HZ				
4 WIRE		SHEET	OF	