FACTORY PROGRAMMING INSTRUCTIONS FOR TJ CINNAMON'S

THE UNIT MUST BE ON BEFORE BEGINNING TO PROGRAM

USE THE DIAL TO CHANGE THE NUMBERS ON THE DISPLAY FOR TIME AND TEMPERATURE

MANUAL BAKE

- 1. PRESS SET KEY TO PROGRAM THE TEMPERATURE.
- 2. PRESS SET KEY AGAIN TO PROGRAM THE FAN.
- 3. PRESS SET KEY AGAIN TO PROGRAM THE TIME.
- 4. PRESS SET KEY AGAIN TO END PROGRAM.

PRE-PROGRAMMED BUTTONS

- 1. PRESS AND HOLD PROG KEY FOR THREE (3) SECONDS ALL THE PRODUCT KEY LEDS LIGHT.
- 2. CODE WILL BE DISPLAYED. PRESS 4-2-7-5 AND THE START/CANCEL KEY. PROD WILL BE DISPLAYED.
- 3. PRESS THE PRODUCT KEY #1. ONCE THE PROGRAMMING FOR PRODUCT KEY #1 IS COMPLETED, REPEAT STEPS 1 & 2 AND PRESS THE APPROPRIATE PRODUCT KEY TO BEGIN PROGRAMMING THE-NEXT BUTTON. THE PROGRAMMING FOR EACH PRODUCT KEY IS SHOWN BELOW. ONCE IN PROGRAM MODE YOU HAVE 10 SECOND TO PRESS A BUTTON OR THE CONTROL WILL EXIT PROGRAM MODE.

START/CANCEL BY PRESSING THIS BUT ON YOU CAN TOGGLE BETWEEN THE AVAILABLE OPTIONS IN PROGRAMMING.

SET BY PRESSING THIS BUTTON YOU ADVANCE TO THE NEXT FEATURE IN PROGRAMMING.

PRODUCT KEY	SHLF	TIME	PRE	TEMP	FAN	ST / FL	· -
	的可以對					原的自動物配	
		:01 min	ein.	270 °F	LO		MANUAL BAKE
語為機能的	政學學的	2.李萨斯的	副的原则是	明祖哪里	导加速压力	建物解析	
1	YES	27 MIN	:00	270 °F	LO	FL	
2 20	YES.	26 MIN	2 多数00函数	#270PF 1	REEQ.	erite:	
3	YES	15 MIN	:00	. 325 °F	LO	FL	
4	LINES.	≟22 MIN⊷	一,100 至中	270%F	HA-LO+ H) FB-6-	
5	YEŞ	:01 min	:00	.270 °F	LO	FL	
6.	YES	- i01 min :	+00 kg	1270°F	#-#LO	r FE	
7	YES	2 MIN	:00	270 °F	LO	FL	
8	YES -	:01 min	15:00 c	270°F	i Lo	FL	
9	YES	2 MIN	:00	325 °F	LO	FL]

** NOTE ** A SOLID COLON INDICATES THE TIMER WILL COUNTDOWN IN MINUTES AND SECONDS, WHILE A FLASHING COLON INDICATES HOURS AND MINUTES